



**GEM-YEAR TESTING LABORATORY
CERTIFICATE OF INSPECTION**

MANUFACTURER: GEM-YEAR INDUSTRIAL CO., LTD.
 ADDRESS: NO.8GEM-YEAR
 ROAD,E.D.Z.JIASHAN,ZHEJIANG,P.R.CHINA
 PURCHASER: MAPTCO FASTENERS (AUST) PTY LTD
 PO. NUMBER: MAP-2011S
 COMMODITY: ISO 4014 HEX HEAD BOLT HALF THREAD CL 8.8
 SIZE: M20-2.50X90
 LOT NO: 1B2030932
 SHIP QUANTITY: 1,200 PCS
 HEADMARKS: GENIUS SYMBOL & 8.8
 COUNTRY OF ORIGIN: CHINA

TEL: (0573) 84185001 (48Lines)
 FAX: (0573) 84184488 84184567
 DATE: 2020/07/10
 PACKING NO: GEM200521016
 INVOICE NO: GEM/MAP-200713SYD
 PART NO: A1138
 SAMPLING PLAN:
 ASME B18.18-2017/ASTM F1470-2018
 HEAT NO: 20100846
 MATERIAL: ML40CR
 FINISH: H. T. PLAIN

PERCENTAGE COMPOSITION OF CHEMISTRY: TEST FACILITY :S

Chemistry	C%	Cr%	Mn%	P%	S%	Si%
Spec.:MIN.	0.3800	0.9000	0.6000			
MAX.	0.4500	1.2000	0.9000	0.0350	0.0350	0.3000
Test Value	0.4100	1.0100	0.7000	0.0140	0.0040	0.1500

DIMENSIONAL INSPECTIONS: ACCORDING TO ISO4014-2011 TEST FACILITY : M

SAMPLED BY: ZHANGHONGYUN

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
THREAD LENGTH	13 PCS	JB/T 9151	46		52.1200-52.4800 MM	13	0
HEIGHT	3 PCS	JB/T 9151		12.2900-12.7100 MM	12.3500-12.4600 MM	3	0
NOMINAL LENGTH	13 PCS	JB/T 9151		89.3000-90.7000 MM	89.4400-89.5100 MM	13	0
WIDTH ACROSS FLATS	3 PCS	JB/T 9151		29.6700-30.0000 MM	29.7100-29.7700 MM	3	0
SURFACE DISCONTINUITIES	18 PCS	ISO6157.3			PASSED	18	0
BODY DIAMETER	3 PCS	JB/T 9151		19.6700-20.0000 MM	19.7200-19.8400 MM	3	0
WIDTH ACROSS CORNERS	3 PCS	JB/T 9151		Min. 33.5300 MM	33.5800-33.6200 MM	3	0
MAJOR DIAMETER	3 PCS	JB/T 9151		19.6300-19.9500 MM	19.6700-19.7500 MM	3	0
THREAD	13 PCS	JB/T 9151		6g GO 6g NOGO	PASSED	13	0

MECHANICAL PROPERTIES: ACCORDING TO ISO 898.1-2013 TEST FACILITY : M

SAMPLED BY: SHACONGBIAO

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
CORE HARDNESS	13 PCS	ISO898.1		23-34 HRC	29-31 HRC	13	0
SURFACE HARDNESS	13 PCS	ISO898.1		Max. 365 HV	292-305 HV	13	0
TENSILE STRENGTH	3 PCS	ISO898.1		Min. 830 N/MM2	928-937 N/MM2	3	0

ALL TESTS ARE IN ACCORDANCE WITH THE METHODS PRESCRIBED IN THE APPLICABLE ASTM/SAE/ASME. SPECIFICATION. WE CERTIFY THAT THIS DATA IS A TRUE REPRESENTATION OF INFORMATION PROVIDED BY THE MATERIAL SUPPLIER AND OUR TESTING LABORATORY.

THE REPORT IS ISSUED ACCORDING TO ISO16228 F3.1(EN10204 3.1)

TYPE M: MANUFACTURER

TYPE S: SUPPLIER(STEEL MILL,PLATING SUB SUPPLIER,HEAT TREATMENT SUB SUPPLIER ETC.)

WE CERTIFY THE PARTS ARE ROHS COMPLIANT.

SIGNATURE: