



**GEM-YEAR TESTING LABORATORY  
CERTIFICATE OF INSPECTION**

MANUFACTURER: GEM-YEAR INDUSTRIAL CO., LTD.  
 ADDRESS: NO.8GEM-YEAR  
 ROAD,E.D.Z.JIASHAN,ZHEJIANG,P.R.CHINA  
 PURCHASER: MAPTCO FASTENERS (AUST) PTY LTD  
 PO. NUMBER: MAP-2016S  
 COMMODITY: ISO 4014 HEX HEAD BOLT HALF THREAD CL 8.8  
 SIZE: M16-2.00X120  
 LOT NO: 1B2041861  
 SHIP QUANTITY: 1,260 PCS  
 HEADMARKS: GENIUS SYMBOL & 8.8  
 COUNTRY OF ORIGIN: CHINA

TEL: (0573) 84185001 (48Lines)  
 FAX: (0573) 84184488 84184567  
 DATE: 2020/07/10  
 PACKING NO: GEM200521016  
 INVOICE NO: GEM/MAP-200713SYD  
 PART NO: A915  
 SAMPLING PLAN:  
 ASME B18.18-2017/ASTM F1470-2018  
 HEAT NO: 20301597  
 MATERIAL: 40ACR  
 FINISH: H. T. PLAIN

PERCENTAGE COMPOSITION OF CHEMISTRY: TEST FACILITY :S

Chemistry	Al%	C%	Cr%	Cu%	Mn%	Ni%	P%	S%	Si%
Spec.:MIN.	0.0100	0.4000	0.2000		0.6000				
MAX.		0.4400	0.4000	0.2000	0.9000	0.2000	0.0250	0.0250	0.1000
Test Value	0.0250	0.4200	0.2800	0.0200	0.7800	0.0100	0.0120	0.0030	0.0800

DIMENSIONAL INSPECTIONS: ACCORDING TO ISO4014-2011 TEST FACILITY : M

SAMPLED BY: ZHANGHONGYUN

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
NOMINAL LENGTH	9 PCS	JB/T 9151		119.3000-120.7000 MM	119.4500-119.5600 MM	9	0
BODY DIAMETER	3 PCS	JB/T 9151		15.7300-16.0000 MM	15.7600-15.8400 MM	3	0
MAJOR DIAMETER	3 PCS	JB/T 9151		15.6900-15.9600 MM	15.7300-15.7800 MM	3	0
HEIGHT	3 PCS	JB/T 9151		9.8200-10.1800 MM	9.8600-9.9200 MM	3	0
WIDTH ACROSS FLATS	3 PCS	JB/T 9151		23.6700-24.0000 MM	23.7400-23.8200 MM	3	0
SURFACE DISCONTINUITIES	11 PCS	IS06157.3			PASSED	11	0
WIDTH ACROSS CORNERS	3 PCS	JB/T 9151		Min. 26.7500 MM	26.7800-26.8400 MM	3	0
THREAD LENGTH	9 PCS	JB/T 9151	38		40.2600-40.4100 MM	9	0
THREAD	3 PCS	JB/T 9151		6g GO 6g NOGO	PASSED	3	0

MECHANICAL PROPERTIES: ACCORDING TO ISO 898.1-2013 TEST FACILITY : M

SAMPLED BY: SHACONGBIAO

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
TENSILE STRENGTH	3 PCS	IS0898.1		Min. 800 N/MM2	880-887 N/MM2	3	0
CORE HARDNESS	9 PCS	IS0898.1		22-32 HRC	28-29 HRC	9	0
SURFACE HARDNESS	9 PCS	ASTM E384		Max. 350 HV	279-290 HV	9	0

ALL TESTS ARE IN ACCORDANCE WITH THE METHODS PRESCRIBED IN THE APPLICABLE ASTM/SAE/ASME. SPECIFICATION. WE CERTIFY THAT THIS DATA IS A TRUE REPRESENTATION OF INFORMATION PROVIDED BY THE MATERIAL SUPPLIER AND OUR TESTING LABORATORY.

THE REPORT IS ISSUED ACCORDING TO ISO16228 F3.1(EN10204 3.1)

TYPE M: MANUFACTURER

TYPE S: SUPPLIER(STEEL MILL,PLATING SUB SUPPLIER,HEAT TREATMENT SUB SUPPLIER ETC.)

WE CERTIFY THE PARTS ARE ROHS COMPLIANT.

SIGNATURE: