



GEM-YEAR TESTING LABORATORY

CERTIFICATE OF INSPECTION

MANUFACTURER : GEM-YEAR INDUSTRIAL CO., LTD.
ADDRESS : NO.8 GEM-YEAR
ROAD,E.D.Z.,JIASHAN,ZHEJIANG,P.R.CHINA

Tel: (0573)84185001(48Lines)
Fax: (0573)84184488 84184567
DATE : 2020/03/10

PURCHASER : MAPTCO FASTENERS (AUST) PTY LTD
PO. NUMBER : MAP-1938M
COMMODITY : FLAT ROUND WASHER --
SIZE : M12
LOT NO : 1E19AF038 (1A2019C1025)
SHIP QUANTITY : 2, 525 PCS
HEADMARKS :

PACKING NO : GEM200103002
INVOICE NO : GEM/MAP-200317MEL
PART NO : G003
SAMPLING PLAN :
ASME B18.18-2017/ASTM F1470-2018
HEAT NO : 19706258
MATERIAL : 45

COUNTRY OF ORIGIN : CHINA

FINISH : H. T. HOT DIP GAL PER ASTM
A153/ASTM F2329

PERCENTAGE COMPOSITION OF CHEMISTRY : TEST FACILITY : S

Chemistry	C%	Mn%	Ni%	P%	S%	Si%
Spec. : MIN.	0.4200	0.5000				0.1700
MAX.	0.5000	0.8000	0.3000	0.0350	0.0350	0.3700
Test Value	0.4500	0.6100	0.0200	0.0110	0.0110	0.2300

DIMENSIONAL INSPECTIONS : ACCORDING TO AS1252-1983 TEST FACILITY: M

SAMPLED BY : ZHANG HUI JING

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC.	REJ.
WASHER OUTSIDE DIAMETER	4PCS	JB/T 9151		25.4000-27.0000 MM	25.8500-26.1200 MM	4	0
WASHER INSIDE DIAMETER	4PCS	JB/T 9151		14.0000-14.4300 MM	14.1500-14.2700 MM	4	0
WASHER THICKNESS	4PCS	JB/T 9151		3.1000-4.6000 MM	3.7200-4.0400 MM	4	0
SURFACE DISCONTINUITIES	29PCS	ISO6157.3			PASSED	29	0

MECHANICAL PROPERTIES : ACCORDING TO AS1252-1996 TEST FACILITY: M

SAMPLED BY : YJUN

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC.	REJ.
CORE HARDNESS	15PCS	ISO898.1		26-45 HRC	40.3-42.7 HRC	15	0
PLATING THICKNESS(μ m)	4PCS	ASTM B568		>=53	67.84-85.86	4	0

ALL TESTS ARE IN ACCORDANCE WITH THE METHODS PRESCRIBED IN THE APPLICABLE ASTM/SAE/ASME/MIL-STD-120 SPECIFICATION. WE CERTIFY THAT THIS DATA IS A TRUE REPRESENTATION OF INFORMATION PROVIDED BY THE MATERIAL SUPPLIER AND OUR TESTING LABORATORY.

THE REPORT IS ISSUED ACCORDING TO ISO16228 F3.1(EN10204 3.1)

TYPE M : MANUFACTURER

TYPE S : SUPPLIER (STEEL MILL, PLATING SUB SUPPLIER, HEAT TREATMENT SUB SUPPLIER ETC.,)

SIGNATURE : _____