



**GEM-YEAR TESTING LABORATORY
CERTIFICATE OF INSPECTION**

MANUFACTURER: GEM-YEAR INDUSTRIAL CO., LTD.
 ADDRESS: NO.8GEM-YEAR
 ROAD,E.D.Z.JIASHAN,ZHEJIANG,P.R.CHINA
 PURCHASER: MAPTCO FASTENERS (AUST) PTY LTD
 PO. NUMBER: MAP-2016F
 COMMODITY: ISO 4032 NUTS CL 6
 SIZE: M10-1.50
 LOT NO: 1N2040535(1A20706791)
 SHIP QUANTITY: 12,000 PCS
 HEADMARKS: GENIUS SYMBOL & 6
 COUNTRY OF ORIGIN: CHINA

TEL: (0573) 84185001 (48Lines)
 FAX: (0573) 84184488 84184567
 DATE: 2020/08/24
 PACKING NO: GEM200804002
 INVOICE NO: GEM/MAP-200825FRE
 PART NO: M819
 SAMPLING PLAN:
 ASME B18.18-2017/ASTM F1470-2018
 HEAT NO: 1912054200
 MATERIAL: 1008A
 FINISH: TRIVALENT ZINC PER ASTM F1941

PERCENTAGE COMPOSITION OF CHEMISTRY: TEST FACILITY :S

Chemistry	Al%	C%	Mn%	P%	S%	Si%
Spec.:MIN.	0.0200					
MAX.		0.1000	0.6000	0.0300	0.0350	0.1000
Test Value	0.0450	0.0900	0.2600	0.0190	0.0050	0.0300

DIMENSIONAL INSPECTIONS: ACCORDING TO ISO 4032 TEST FACILITY : M

SAMPLED BY: ZHONGLI

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
WIDTH ACROSS CORNERS	4 PCS	JB/T 9151		Min. 17.7700 MM	17.7700-17.8100 MM	4	0
SURFACE DISCONTINUITIES	29 PCS	IS06157			PASSED	29	0
THICKNESS	4 PCS	JB/T 9151		8.0400-8.3000 MM	8.1100-8.2100 MM	4	0
WIDTH ACROSS FLATS	4 PCS	JB/T 9151		15.7300-16.0000 MM	15.8100-15.9200 MM	4	0
THREAD	15 PCS	JB/T 9151		6H GO 6H NOGO	PASSED	15	0

MECHANICAL PROPERTIES: ACCORDING TO ISO898.2 TEST FACILITY : M

SAMPLED BY: WANGXIAOLAN

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
CORE HARDNESS	15 PCS	IS0898.2		150-302 HV	228-252 HV	15	0
PROOF LOAD	4 PCS	IS0898.2		Min. 4,020 KGF	OK	4	0

ALL TESTS ARE IN ACCORDANCE WITH THE METHODS PRESCRIBED IN THE APPLICABLE ASTM/SAE/ASME. SPECIFICATION. WE CERTIFY THAT THIS DATA IS A TRUE REPRESENTATION OF INFORMATION PROVIDED BY THE MATERIAL SUPPLIER AND OUR TESTING LABORATORY.

THE REPORT IS ISSUED ACCORDING TO ISO16228 F3.1(EN10204 3.1)

TYPE M: MANUFACTURER

TYPE S: SUPPLIER(STEEL MILL,PLATING SUB SUPPLIER,HEAT TREATMENT SUB SUPPLIER ETC.,)

WE CERTIFY THE PARTS ARE ROHS COMPLIANT.

SIGNATURE: