



**GEM-YEAR TESTING LABORATORY  
CERTIFICATE OF INSPECTION**

MANUFACTURER: GEM-YEAR INDUSTRIAL CO., LTD.  
 ADDRESS: NO.8GEM-YEAR  
 ROAD,E.D.Z.JIASHAN,ZHEJIANG,P.R.CHINA  
 PURCHASER: MAPTCO FASTENERS (AUST) PTY LTD  
 PO. NUMBER: MAP-2016S  
 COMMODITY: ISO 4014 HEX HEAD BOLT HALF THREAD CL 10.9  
 SIZE: M20-2.50X90  
 LOT NO: 1B2041842  
 SHIP QUANTITY: 880 PCS  
 HEADMARKS: GENIUS SYMBOL & 10.9  
 COUNTRY OF ORIGIN: CHINA

TEL: (0573) 84185001 (48Lines)  
 FAX: (0573) 84184488 84184567  
 DATE: 2020/09/07  
 PACKING NO: GEM200824006  
 INVOICE NO: GEM/MAP-200907SYD  
 PART NO: A1139  
 SAMPLING PLAN:  
 ASME B18.18-2017/ASTM F1470-2018  
 HEAT NO: C376216A  
 MATERIAL: SCM435  
 FINISH: H. T. TRIVALENT ZINC 5U HYDROGEN  
 RELEASE

**PERCENTAGE COMPOSITION OF CHEMISTRY: TEST FACILITY :S**

Chemistry	C%	Cr%	Mn%	Mo%	Ni%	P%	S%	Si%
Spec.:MIN.	0.3300	0.9000	0.6000	0.1500				0.1500
MAX.	0.3800	1.2000	0.8500	0.3000	0.2500	0.0250	0.0250	0.3500
Test Value	0.3600	1.0000	0.6600	0.1800	0.0200	0.0080	0.0020	0.2400

**DIMENSIONAL INSPECTIONS: ACCORDING TO ISO4014-2011 TEST FACILITY : M**

SAMPLED BY: YANGLI

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
THREAD LENGTH	13 PCS	JB/T 9151	46		52.6300-53.0000 MM	13	0
HEIGHT	3 PCS	JB/T 9151		12.2900-12.7100 MM	12.5000-12.5200 MM	3	0
NOMINAL LENGTH	13 PCS	JB/T 9151		89.3000-90.7000 MM	90.1500-90.3400 MM	13	0
WIDTH ACROSS FLATS	3 PCS	JB/T 9151		29.6700-30.0000 MM	29.7700-29.8300 MM	3	0
SURFACE DISCONTINUITIES	18 PCS	ISO6157.3			PASSED	18	0
BODY DIAMETER	3 PCS	JB/T 9151		19.6700-20.0000 MM	19.7300-19.8100 MM	3	0
WIDTH ACROSS CORNERS	3 PCS	JB/T 9151		Min. 33.5300 MM	33.9500-33.9800 MM	3	0
MAJOR DIAMETER	3 PCS	JB/T 9151		19.6300-19.9500 MM	19.8900-19.9300 MM	3	0
THREAD	13 PCS	JB/T 9151		6h GO 6h NOGO	PASSED	13	0

**MECHANICAL PROPERTIES: ACCORDING TO ISO 898.1-2013 TEST FACILITY : M**

SAMPLED BY: NIESUYING

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
TENSILE STRENGTH	3 PCS	ISO898.1		Min. 1,040 N/MM2	1,056-1,120 N/MM2	3	0
CORE HARDNESS	13 PCS	ISO898.1		32-39 HRC	35-38 HRC	13	0
SURFACE HARDNESS	13 PCS	ASTM E384		Max. 390 HV	363-379 HV	13	0

ALL TESTS ARE IN ACCORDANCE WITH THE METHODS PRESCRIBED IN THE APPLICABLE ASTM/SAE/ASME. SPECIFICATION. WE CERTIFY THAT THIS DATA IS A TRUE REPRESENTATION OF INFORMATION PROVIDED BY THE MATERIAL SUPPLIER AND OUR TESTING LABORATORY.

THE REPORT IS ISSUED ACCORDING TO ISO16228 F3.1(EN10204 3.1)

TYPE M: MANUFACTURER

TYPE S: SUPPLIER(STEEL MILL,PLATING SUB SUPPLIER,HEAT TREATMENT SUB SUPPLIER ETC.,)

WE CERTIFY THE PARTS ARE ROHS COMPLIANT.

SIGNATURE: