



**GEM-YEAR TESTING LABORATORY  
CERTIFICATE OF INSPECTION**

MANUFACTURER: GEM-YEAR INDUSTRIAL CO., LTD.  
 ADDRESS: NO.8GEM-YEAR  
 ROAD,E.D.Z.JIASHAN,ZHEJIANG,P.R.CHINA  
 PURCHASER: MAPTCO FASTENERS (AUST) PTY LTD  
 PO. NUMBER: MAP-2036M  
 COMMODITY: ISO 4014 HEX HEAD BOLT HALF THREAD CL 8.8  
 SIZE: M10-1.50X60  
 LOT NO: 1B2090676  
 SHIP QUANTITY: 10,000 PCS  
 HEADMARKS: GENIUS SYMBOL & 8.8  
 COUNTRY OF ORIGIN: CHINA

TEL: (0573) 84185001 (48Lines)  
 FAX: (0573) 84184488 84184567  
 DATE: 2020/10/27  
 PACKING NO: GEM200927003  
 INVOICE NO: GEM/MAP-201026MEL  
 PART NO: A289  
 SAMPLING PLAN:  
 ASME B18.18-2017/ASTM F1470-2018  
 HEAT NO: 20306586  
 MATERIAL: 35ACR  
 FINISH: H. T. TRIVALENT ZINC PER ASTM F1941

PERCENTAGE COMPOSITION OF CHEMISTRY: TEST FACILITY :S

Chemistry	Al%	C%	Cr%	Mn%	P%	S%	Si%
Spec.:MIN.	0.0100	0.3500	0.2000	0.6000			
MAX.		0.3900	0.4000	0.9000	0.0250	0.0250	0.1000
Test Value	0.0380	0.3800	0.2600	0.7700	0.0140	0.0060	0.0700

DIMENSIONAL INSPECTIONS: ACCORDING TO ISO4014-2011 TEST FACILITY : M

SAMPLED BY: ZHONGLI

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
MAJOR DIAMETER	4 PCS	JB/T 9151		9.7400-9.9600 MM	9.7400-9.9600 MM	4	0
HEIGHT	4 PCS	JB/T 9151		6.2200-6.5800 MM	6.2200-6.5800 MM	4	0
WIDTH ACROSS CORNERS	4 PCS	JB/T 9151		Min. 17.7700 MM	17.7700-17.7800 MM	4	0
BODY DIAMETER	4 PCS	JB/T 9151		9.7800-10.0000 MM	9.7800-10.0000 MM	4	0
WIDTH ACROSS FLATS	4 PCS	JB/T 9151		15.7300-16.0000 MM	15.7300-16.0000 MM	4	0
SURFACE DISCONTINUITIES	29 PCS	IS06157.3			PASSED	29	0
THREAD LENGTH	15 PCS	JB/T 9151	26		26.1000-26.1100 MM	15	0
NOMINAL LENGTH	15 PCS	JB/T 9151		59.4000-60.6000 MM	59.4000-60.6000 MM	15	0
THREAD	4 PCS	JB/T 9151		6h GO 6h NOGO	PASSED	4	0

MECHANICAL PROPERTIES: ACCORDING TO ISO 898.1-2013 TEST FACILITY : M

SAMPLED BY: NIESUYING

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
TENSILE STRENGTH	4 PCS	IS0898.1		Min. 800 N/MM2	880-900 N/MM2	4	0
CORE HARDNESS	15 PCS	IS0898.1		22-32 HRC	29-30 HRC	15	0
SURFACE HARDNESS	15 PCS	ASTM E384		Max. 350 HV	290-315 HV	15	0

ALL TESTS ARE IN ACCORDANCE WITH THE METHODS PRESCRIBED IN THE APPLICABLE ASTM/SAE/ASME. SPECIFICATION. WE CERTIFY THAT THIS DATA IS A TRUE REPRESENTATION OF INFORMATION PROVIDED BY THE MATERIAL SUPPLIER AND OUR TESTING LABORATORY.

THE REPORT IS ISSUED ACCORDING TO ISO16228 F3.1(EN10204 3.1)

TYPE M: MANUFACTURER

TYPE S: SUPPLIER(STEEL MILL,PLATING SUB SUPPLIER,HEAT TREATMENT SUB SUPPLIER ETC.)

WE CERTIFY THE PARTS ARE ROHS COMPLIANT.

SIGNATURE: