



**GEM-YEAR TESTING LABORATORY  
CERTIFICATE OF INSPECTION**

MANUFACTURER: GEM-YEAR INDUSTRIAL CO., LTD.  
 ADDRESS: NO.8GEM-YEAR  
 ROAD,E.D.Z.JIASHAN,ZHEJIANG,P.R.CHINA  
 PURCHASER: MAPTCO FASTENERS (AUST) PTY LTD  
 PO. NUMBER: MAP-2029F  
 COMMODITY: ISO 4014 HEX HEAD BOLT HALF THREAD CL 8.8  
 SIZE: M16-2.00X80  
 LOT NO: 1B2072335  
 SHIP QUANTITY: 3,300 PCS  
 HEADMARKS: GENIUS SYMBOL & 8.8  
 COUNTRY OF ORIGIN: CHINA

TEL: (0573) 84185001 (48Lines)  
 FAX: (0573) 84184488 84184567  
 DATE: 2020/09/09  
 PACKING NO: GEM200824007  
 INVOICE NO: GEM/MAP-200911FRE  
 PART NO: A888  
 SAMPLING PLAN:  
 ASME B18.18-2017/ASTM F1470-2018  
 HEAT NO: 20206590  
 MATERIAL: 40ACR  
 FINISH: H. T. PLAIN

PERCENTAGE COMPOSITION OF CHEMISTRY: TEST FACILITY :S

Chemistry	C%	Cr%	Mn%	P%	S%	Si%
Spec.:MIN.	0.4000	0.2000	0.6000			
MAX.	0.4400	0.4000	0.9000	0.0250	0.0250	0.1000
Test Value	0.4200	0.2700	0.7500	0.0090	0.0070	0.0700

DIMENSIONAL INSPECTIONS: ACCORDING TO ISO4014-2011 TEST FACILITY : M

SAMPLED BY: ZHANGHONGYUN

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
WIDTH ACROSS FLATS	4 PCS	JB/T 9151		23.6700-24.0000 MM	23.8600-23.8800 MM	4	0
NOMINAL LENGTH	15 PCS	JB/T 9151		79.4000-80.6000 MM	80.0300-80.2600 MM	15	0
BODY DIAMETER	4 PCS	JB/T 9151		15.7300-16.0000 MM	15.8600-15.8800 MM	4	0
MAJOR DIAMETER	4 PCS	JB/T 9151		15.6900-15.9600 MM	15.8600-15.8800 MM	4	0
THREAD LENGTH	15 PCS	JB/T 9151	38		38.5200-38.6900 MM	15	0
HEIGHT	4 PCS	JB/T 9151		9.8200-10.1800 MM	10.0200-10.0400 MM	4	0
SURFACE DISCONTINUITIES	22 PCS	ISO6157.3			PASSED	22	0
WIDTH ACROSS CORNERS	4 PCS	JB/T 9151		Min. 26.7500 MM	26.9200-26.9500 MM	4	0
THREAD	15 PCS	JB/T 9151		6g GO 6g NOGO	PASSED	15	0

MECHANICAL PROPERTIES: ACCORDING TO ISO 898.1-2013 TEST FACILITY : M

SAMPLED BY: NIESUYING

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
TENSILE STRENGTH	4 PCS	ISO898.1		Min. 800 N/MM2	910-921 N/MM2	4	0
CORE HARDNESS	15 PCS	ISO898.1		22-32 HRC	25-29 HRC	15	0
SURFACE HARDNESS	15 PCS	ASTM E384		Max. 350 HV	298-304 HV	15	0

ALL TESTS ARE IN ACCORDANCE WITH THE METHODS PRESCRIBED IN THE APPLICABLE ASTM/SAE/ASME. SPECIFICATION. WE CERTIFY THAT THIS DATA IS A TRUE REPRESENTATION OF INFORMATION PROVIDED BY THE MATERIAL SUPPLIER AND OUR TESTING LABORATORY.

THE REPORT IS ISSUED ACCORDING TO ISO16228 F3.1(EN10204 3.1)

TYPE M: MANUFACTURER

TYPE S: SUPPLIER(STEEL MILL,PLATING SUB SUPPLIER,HEAT TREATMENT SUB SUPPLIER ETC.)

WE CERTIFY THE PARTS ARE ROHS COMPLIANT.

SIGNATURE: