



**GEM-YEAR TESTING LABORATORY  
CERTIFICATE OF INSPECTION**

MANUFACTURER: GEM-YEAR INDUSTRIAL CO., LTD.  
 ADDRESS: NO.8GEM-YEAR  
 ROAD,E.D.Z.JIASHAN,ZHEJIANG,P.R.CHINA  
 PURCHASER: MAPTCO FASTENERS (AUST) PTY LTD  
 PO. NUMBER: MAP-2031S  
 COMMODITY: HEX CAP SCREW GR-8  
 SIZE: 1/2-13X4-1/2 NC  
 LOT NO: 1B2073138  
 SHIP QUANTITY: 1,750 PCS  
 HEADMARKS: GENIUS SYMBOL & 6 RADIAL LINES  
 COUNTRY OF ORIGIN: CHINA

TEL: (0573) 84185001 (48Lines)  
 FAX: (0573) 84184488 84184567  
 DATE: 2020/10/16  
 PACKING NO: GEM200918001  
 INVOICE NO: GEM/MAP-201019SYD  
 PART NO: D059  
 SAMPLING PLAN:  
 ASME B18.18-2017/ASTM F1470-2018  
 HEAT NO: 19365270  
 MATERIAL: SCM435  
 FINISH: H. T. PLAIN

PERCENTAGE COMPOSITION OF CHEMISTRY: TEST FACILITY :S

Chemistry	C%	Cr%	Mn%	Mo%	Ni%	P%	S%	Si%
Spec.:MIN.	0.3300	0.9000	0.6000	0.1500				0.1500
MAX.	0.3800	1.2000	0.8500	0.3000	0.2500	0.0250	0.0250	0.3500
Test Value	0.3500	1.0000	0.6400	0.2200	0.0400	0.0070	0.0020	0.2300

DIMENSIONAL INSPECTIONS: ACCORDING TO ASME B18.2.1-2012 TEST FACILITY : M

SAMPLED BY: ZHANGHONGYUN

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
WIDTH ACROSS CORNERS	4 PCS	JIS B1071		21.3400-21.9900 MM	21.6300-21.6600 MM	4	0
THREAD LENGTH	15 PCS	JIS B1071	31.75		31.9200-31.9500 MM	15	0
MAJOR DIAMETER	4 PCS	JIS B1071		12.3900-12.6600 MM	12.5000-12.5200 MM	4	0
WIDTH ACROSS FLATS	4 PCS	JIS B1071		18.7000-19.0500 MM	18.8600-18.8800 MM	4	0
NOMINAL LENGTH	15 PCS	JIS B1071		111.7600-114.3000 MM	112.5200-112.8000 MM	15	0
SURFACE DISCONTINUITIES	22 PCS	ASTM F788/F788M			PASSED	22	0
BODY DIAMETER	4 PCS	JIS B1071		12.5300-12.7000 MM	12.6300-12.6600 MM	4	0
HEIGHT	4 PCS	JIS B1071		7.6800-8.2000 MM	8.0300-8.0600 MM	4	0
THREAD	15 PCS	JIS B1071		2A GO 2A NOGO	PASSED	15	0

MECHANICAL PROPERTIES: ACCORDING TO SAE J 429-2014 TEST FACILITY : M

SAMPLED BY: CHENGMINGHANG

INSPECTIONS ITEM	SAMPLE	TEST METHOD	REF	SPECIFIED	ACTUAL RESULT	ACC	REJ
CORE HARDNESS	15 PCS	ASTM F606/F606M		33-39 HRC	36-37 HRC	15	0
TENSILE STRENGTH	4 PCS	ASTM F606/F606M		Min. 150 KSI	161-168 KSI	4	0
SURFACE HARDNESS	15 PCS	ASTM F606/F606M		Max. 58.6 HR30N	55-57 HR30N	15	0

ALL TESTS ARE IN ACCORDANCE WITH THE METHODS PRESCRIBED IN THE APPLICABLE ASTM/SAE/ASME. SPECIFICATION. WE CERTIFY THAT THIS DATA IS A TRUE REPRESENTATION OF INFORMATION PROVIDED BY THE MATERIAL SUPPLIER AND OUR TESTING LABORATORY.

THE REPORT IS ISSUED ACCORDING TO ISO16228 F3.1(EN10204 3.1)

TYPE M: MANUFACTURER

TYPE S: SUPPLIER(STEEL MILL,PLATING SUB SUPPLIER,HEAT TREATMENT SUB SUPPLIER ETC.)

WE CERTIFY THE PARTS ARE ROHS COMPLIANT.

SIGNATURE: